# This Page Is Inserted by IFW Operations and is not a part of the Official Record

# BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

# IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.







## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:

C08J 9/00, 3/00, E01C 13/00

(11) International Publication Number:

WO 92/19669

(43) International Publication Date:

12 November 1992 (12.11.92)

(21) International Application Number:

PCT/GB92/00782

A1

(22) International Filing Date:

28 April 1992 (28.04.92)

(30) Priority data:

9109536.4

2 May 1991 (02.05.91)

(71)(72) Applicant and Inventor: BOWERS, Frank [GB/GB]; P.O. Box 1, Hoby, Melton Mowbray, Leicestershire LE14 3DT (GB).

(74) Agent: LAWRENCE, John, Gordon; McNeight & Lawrence, Regent House, Heaton Lane, Stockport SK4 1BS (GB).

(81) Designated States: AT, AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI patent), BR, CA, CF (OAPI patent), CG (OAPI patent), CH, CH (European patent), CI (OAPI patent), CM (OAPI patent), CS, DE, DE (European patent), DK, DK (European patent), ES, ES (European patent), FI, FR (European patent), CA (OAPI patent), CR (CR) pean patent), ES, ES (European patent), FI, FR (European patent), GA (OAPI patent), GB, GB (European patent), GN (OAPI patent), GR (European patent), HU, IT (European patent), JP, KP, KR, LK, LU, LU (European patent), MC (European patent), MG, ML (OAPI patent), MN, MR (OAPI patent), MW, NL, NL (European patent), NO, PL, RO, RU, SD, SE, SE (European patent), SN (OAPI patent), TD (OAPI patent), TG (OAPI patent), IS tent), US.

Published

With international search report.

(54) Title: POLYMERIC COMPOSITIONS

#### (57) Abstract

There is disclosed a method of producing a porous composite comprising the steps of : pre-wetting particulate material with a liquid curing agent medium to form a stable intermediate; transporting the intermediate to site; forming a shaped mass of the intermediate; and applying to the intermediate a liquid polymer or pre-polymer, either immediately before or after formation of said mass.

attention 5219669AD

### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

ΑŦ	Austria	FI	Finlant.	мі	Mali
AU	Australia	FR	France	MN	Mongolia
88	Barbalos	GA	Ciabon	MIR	Mauritania
86	Belgium	GB	United Kingdom	MW	Malawi
86	Burkina Faso	GN	Guinea	NI.	Netherlands
86	Bulgaria	GH	Greece	NO	Norway
BJ	Benin	HU	Hungary	PL	Poland
RK	Brazil	1E	Ireland	RO	Linung
CA	Canada	rr	fialy	RU	Russian Federation
CF	Central African Republic	JP	Japan	SD	Siidan
CG	Congo	KP	Democratic People's Republic	SE	Sweiten
CII	Switzerland		of Korea	SN	Senegal
CI	Côte d'Ivaire	KK	Republic of Korea	SU	Soviet Union
CAI	Cameroon	LI	Licchtenstein	TD	Chad
CS	Czechoslovakia	LK	Sri Lanta	TG	Togo
DE	Ciermany	LU	Luxentourg	us	United States of America
OK	Denmark	NIC	Monaco		
	_				

Madagascar

Spain

## POLYMERIC COMPOSITIONS

This invention concerns methods and materials for the production of polymeric compositions, particularly, though by no means exclusively, suitable for use in the formation of impact absorbing surfaces or substrates to sports or play areas.

Known such impact absorbing surfaces comprise crumbs of a natural or synthetic rubber, such as EPDM for example, in a matrix of polymer, such as polyurethane for example.

The matrix may completely fill the spaces
between the crumbs to give a non-porous composition or
may simply coat the surfaces of the crumbs to cause them
to adhere leaving the interstices between the crumbs
void to give a porous product.

Either kind of composition may be laid to form a sports or play surface or to form a substrate to another surface such as that provided by synthetic turf for example.

The compositions are prepared on site immediately before use by mixing crumb, liquid polymer and if necessary a catalyst, to enable them to be laid, in the manner of asphalt, before polymerization has advanced

sufficiently to render them unworkable. Advantageously polymerization times are short to reduce the risk of damage to the finished surface before it has set.

The on site preparation and short setting time neccessitates expensive equipment and highly trained operators regardless of the size of the project.

It is an object of the present invention to provide a method and materials for production of a porous composite which overcomes the disadvantage aforesaid.

According to the present invention there is provided a method of producing a porous composite comprising the steps of :-

pre-wetting particulate material with a liquid curing agent medium to form a stable intermediate;

transporting the intermediate to site; forming a shaped mass of the intermediate; and

applying to the intermediate a liquid polymer or pre-polymer, either immediately before or after formation of said mass.

The shaped mass may be a horizontal layer.

The liquid polymer or pre-polymer may be in the form of an emulsion.

The liquid polymer or pre-polymer may include an inhibitor or retarder to give extended shelf life.

The liquid medium may contain a catalyst or a chemical to neutralise any inhibitor or retardant present in the liquid polymer or pre-polymer.

The liquid medium may contain a coupling agent.

The liquid medium may contain a diluent.

The particulate material may be a natural or synthetic rubber crumb.

The intermediate may be mixed with the liquid polymer or pre-polymer for a predetermined short period before formation of the shaped mass.

The mixing may be effected using a conventional cement mixer.

The liquid polymer or pre-polymer may be applied to the shaped mass by spraying or pouring.

The invention also includes compositions for use in practising the methods aforesaid.

The invention will be further apparent from the following description, which concerns, by way of example only, the laying of a running-track in accordance with one method thereof.

In general the invention comprises pre-wetting a rubber crumb with a curing agent to form a stable intermediate, at a central facility. The intermediate is bagged for storage and transport to site.

Onto a suitable sub-base a base coat comprising the intermediate is laid using conventional concrete or asphalt laying techniques and equipment.

An emulsion of polymer or pre-polymer is then sprayed over the crumb surface so as to pass through the interstices of the mix to join the crumbs into a coherent mass. Excess liquid disperses into the sub-base.

In an alternative approach the intermediate is mixed with the polymer or pre-polymer for a predetermined short time using a conventional cement mixer to initiate polymerisation before the mix is laid.

In a specific example SBR waste rubber granules having sizes in the range of 2mm - 6mm are coated with 2% by weight of a liquid medium comprising a hydraulically stable organic polyol containing the polyurethane catalyst dibutyltin mercaptide and a coupling agent (silane). The mixture is bagged for storage and use at a later date. The shelf life of the bagged mixture is greater than 12 months.

A Diphenylmethane -4, 4' Di-Isocyanate based pre-polymer having a free (-NCO) of between 8.5% and 9.5% with a viscosity of between 2800 and 3400 cp is prepared and bottled. The shelf life of pre-polymer is up to 12 months.

When required the bags of pre-wetted rubber granules and bottles of pre-polymer are transported to site.

The pre-wetted granules and pre-polymer are mixed (1 litre of pre-polymer to 40 kg of granules) by tumbling in a conventional cement mixer for between three and five minutes.

The final mixture is then laid onto a prepared sub-base and allowed to polymerise.

Polymerisation time is controlled by adjusting the amount of catalyst pre-mixed with the rubber granules.

It will be appreciated that it is not intended to limit the invention to the above example only, many variations, such as might readily occur to one skilled in the art, being possible, without departing from the scope thereof as defined by the appended claims.

Whilst the specific example is concerned with a polyurethane resin system it will be understood that other systems such as epoxy resin systems might be used.

Again, for example, the particulate material may comprise cork crumb, gravel, chipped bark or any other material suited to the intended application.

Yet again, for example, the composition may include fillers, colouring materials or other known additives.

# <u>CLAIMS</u>

1. A method of producing a porous composite comprising the steps of :-

pre-wetting particulate material with a liquid curing agent medium to form a stable intermediate; transporting the intermediate to site; forming a shaped mass of the intermediate; and applying to the intermediate a liquid polymer or pre-polymer, either immediately before or after formation of said mass.

- 2. A method according to claim 1, wherein the shaped mass is a horizontal layer.
- 3. A method according to claim 1 or claim 2, wherein the liquid polymer or pre-polymer is in the form of an emulsion.
- 4. A method according to claim 3, wherein the liquid polymer or pre-polymer includes an inhibitor or retarder to give extended shelf life.
- 5. A method according to any preceding claim, wherein the liquid medium contains a catalyst or a

chemical to neutralise any inhibitor or retarder present in the liquid polymer or pre-polymer.

- 6. A method according to any preceding claim, wherein the liquid medium contains a coupling agent.
- 7. A method according to any preceding claim wherein the liquid medium contains a diluent.
- 8. A method according to any preceding claim, wherein the particulate material is a natural or synthetic rubber crumb.
- 9. A method according to any preceding claim, wherein the intermediate is mixed with the liquid polymer or pre-polymer for a predetermined short period before formation of the shaped mass.
- 10. A method according to claim 9, wherein the mixing is effected using a conventional cement mixer.
- 11. A method according to any one of claims 1-8 wherein the liquid polymer or pre-polymer is applied to the shaped mass by spraying or pouring.
- 12. A method according to any preceding claim, wherein the polymer or pre-polymer is a polyurethane based on Diphenylmethane -4, 4' Di-Isocyanate.

13. Bags of pre-wetted particles and containers of polymer or pre-polymer suitable for use in the method of any of claims 1-12.



International Application No PCT/GB 92/00782

1 01 455	IEICATIO	OF SUBJECT MATTER (if several classificat	ion symbols apply, indicate all) <sup>6</sup>		
According	to loterna	tional Patent Classification (IPC) or to both Natio	onal Classification and IPC		
IPC5: C	08 J	9/00, 3/00, E 01 C 13/00			
II. FIELDS	SEARCH	ED			
		Minimum Documental			
Classification	on System	Clas	ssification Symbols		
		•			
		C 08 J; E 01 C			
IPC5		Documentation Searched other th	on Minimum Documentation		
		to the Extent that such Documents a	re included in Fields Searched <sup>8</sup>		
		TO DE DELEMANT			
	MENTS C	ONSIDERED TO BE RELEVANT <sup>9</sup> ion of Document, <sup>11</sup> with indication, where appro	priate, of the relevant passages 12	Relevant to Claim No.13	
Category *	Citat	ion of Document," with Indication, whate spire	May 1991	1-2,4-5,	
P,X	WO, A	l, 9106594 (BOWERS FRANK) 16 ee claims 1-3, 5, 10-11	, may 1991,	8,11	
х	US, A	, 4107100 (JOSEF PETERHANS   5 August 1978,	ET AL)	1-5,8, 11,12	
	l e	ee column 2. line 30 - line	64; column		
}	1 3	line 40 - line 54; column	o, line a		
1	l i	ine 8; abstract; claims 1-5			
l	1				
1	l				
A	EP, A	1, 0165895\(ALBERT FATIO) 2 ee the whole document	7 December 1985,	1-13	
İ	1	•			
]	1	<b></b>			
	}			1	
1	1 .				
1		•	·	}	
1	1				
* Spec	cial catego	pries of cited documents: 10 dining the general state of the art which is not one of particular relevance	"T" later document published after of priority date and not in cont cited to understand the princip invention.	the international filing date lict with the application but lic or theory underlying the	
.E. 6	considered to be of particular relevance  "E" earlier document but published on or after the international filing date  "X" document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step				
٠٢. ۾	ocument w	hich may throw doubts on priority claim(s) or ad to establish the publication date of another ther apecial reason (as specified)	"Y" document of particular releval cannol be considered to involve document is combined with or ments, such combination being	nce, the claimed invention we an inventive step when the	
-0- 4	locument M	sterring to an oral disclosure, use, exhibition or	in the are-		
*P* d	ocument pater than li	ublished prior to the international filing date but ne priority date claimed	"&" document member of the sam	e patent family	
IV CER	TIFICATIO	ON	Date of Mailing of this International	Search Report	
Date of the Actual Completion of the International Search 20th July 1992			0 4 AUG 1992'		
1			Signature of Authorized Officer		
International Searching Authority					
		OPEAN PATENT OFFICE	D. JARVMAN		
Form PCT	715A/210 (	second sheet) (January 1985)			

International Application No. PCT/GB 92/00782

	International Application 115.				
- POCI	MENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)	Relevant to Claim No			
alegory •	MENTS CONSIDERED TO BE RELEVANT (CONTINCED IN STREET OF THE PROPERTY OF THE PR				
	DE, B, 1658488 (A. KOHL & SÖHNE) 23 March 1972,	1-13			
	see the whole document				
	<del></del>				
A	DE, A, 2110327 (HERBERT ALLWELT) 21 September 1972, see the whole document	1-13			
	see the whole document				
İ					
	·				
		ŀ			
1					
l					
ľ					
1					
}					
	·				
1					
1	DET/TSA/210 (extra sheet) (January 1985)				